## WHAT IS CLAIMED IS:

10

15

- 1. A method of water analysis for detecting the presence of microorganisms in a water sample, comprising the step of staining the microorganisms with potassium permanganate (KMnO<sub>4</sub>).
- 2. A method of water analysis for detecting the presence of microorganisms in a water sample, comprising the steps of:

providing a bio-membrane as a filter;

filtering out the microorganisms in the water sample, using the bio-membrane;

cultivating the microorganisms on the bio-membrane;

staining the microorganisms on the bio-membrane with potassium permanganate (KMnO<sub>4</sub>);

rinsing the bio-membrane with purified deionized water, and

performing a colony count for readable microorganisms on the bio-membrane.

3. The method of water analysis according to claim 2, wherein the pore

5

10

15

size of the bio-membrane is about 0.3 µm in diameter.

- 4. The method of water analysis according to claim 2, wherein the water sample is filtered through the bio-membrane by a vacuum filtration technique.
- 5. The method of water analysis according to claim 2, wherein the microorganisms are cultivated on the bio-membrane at about 30°C, using 2 ml of nutrient solution.
- 6. The method of water analysis according to claim 2, wherein the concentration of KMnO<sub>4</sub> is about 0.02 M (mole per liter).
- 7. The method of water analysis according to claim 2, wherein the microorganisms on the bio-membrane are stained with KMnO<sub>4</sub> for about 10 to 30 seconds and then the bio-membrane is rinsed with purified deionized water.
- 8. A method of water analysis for separately detecting the presence of microorganisms in a plurality of water samples, comprising the steps of:
  - providing a plurality of bio-membranes as filters;

filtering out the microorganisms in each of the water samples, using a corresponding bio-membrane, separately;

5

10

15

cultivating the microorganisms on different bio-membranes for different time period;

staining the microorganisms on each of the bio-membranes with potassium permanganate (KMnO<sub>4</sub>);

rinsing each of the bio-membranes with purified deionized water; and

performing a colony count for readable microorganisms on each of the bio-membranes.

- 9. The method of water analysis according to claim 8, wherein the pore size of the bio-membrane is about 0.3 µm in diameter.
- 10. The method of water analysis according to claim 8, wherein each of the water samples is filtered through a corresponding bio-membrane by a vacuum filtration technique.
- 11. The method of water analysis according to claim 8, wherein the microorganisms are cultivated on each of the bio-membranes at about 30°C, using 2 ml of nutrient solution.
- 12. The method of water analysis according to claim 8, wherein the microorganisms on each of the bio-membranes are cultivated for 24, 48, 72,

Assignee's ref. AU0303015 SUNDIAL's ref. US1206F

SUNDIAL CONFIDENTIAL

and 96 hours, respectively.

about 10 to 30 seconds.

5

13. The method of water analysis according to claim 8, wherein the concentration of KMnO<sub>4</sub> is about 0.02 M (mole per liter).

14. The method of water analysis according to claim 8, wherein the microorganisms on each of the bio-membrane are stained with KMnO<sub>4</sub> for

\* \* \* \* \*